3500/3700

Hustler All-Wheel-Drive Diesel

- 30 or 36 hp Shibaura liquid-cooled diesel engine for increased engine life
- Front-mounted, welded XR-7 deck, with tool-free installation
- Side-Discharge Decks rotate up 90° with PTO shaft remaining connected for easier maintanence
- Cruise control and tilt and telescoping steering wheel
- Foldable, two-post ROPS

Best Warranty In Its Class

- Tractor - 2 Year/1500 hour limited Parts & Service*
- Engine - 3 Year/2000 hour limited Parts & Service*

** See your Certified Industrial Hustler dealer for complete details*

HUSTLER

800.395.4757 • www.hustlerturf.com

601645 3-08

3500/3700 All Wheel Drive Diesel Specifications

Hustler AWD Diesel Specifications

Engine

Model	Hustler 3500	Hustler 3700
Horsepower/RPM	30/2,700	36/2,700
No. of Cylinders	3	3
Displacement	1496	1662
Max. Torque	70.8 ft lbs @ 1800 rpm	77.4 ft lbs @ 1800 rpm

Type Liquid-cooled, inline, 3-cylinder, normally aspirated industrial diesel engine
Starter 12-volt (1.2 kw), solenoid shift positive engagement
Ignition Electronic
Charging System 12-volt, 40-amp alternator
Oil Filter Spin-on engine oil filter 6.3 Qt (6.0 l) oil capacity
Engine Oil 10W30
Fuel #2 diesel
Fuel Filter Heavy-duty, spin-on fuel filter
Injection System Bosch in-line
Air Filter Heavy-duty air filter with safety filter for maximum protection, dry, dual-element
Cooling Liquid cooled. Direct-driven, mechanical cooling fan
Governor Mechanical governor with 2700 RPM high idle speed
PTO Independent type PTO. PTO speed 2209 RPM

Traction Drive System

Type Auto 4WD or Full time 4WD

Filter 30 micron, in tank
Ground Speed Forward Low: 0-6 mph, High: 0-15 mph Reverse Low: 0-4, High: 0-9
Steering Hydrostatic power. Tilt & telescoping steering wheel
Speed Control 2 pedals forward & reverse. 2 range hydrostatic transmission, Cruise control
Brakes Wet disc (Single pedal control)

Tires Front Drive 24 x 12 – 12, turf tread, Rear Drive 20 x 8 -10
Capacities Fuel System: 13 US gal (49.2)
Weight (Tractor) 1777lbs (806 Kg)

Dimensions Height: 53 in (130 cm) ROPS folded down
77 in (175 cm) ROPS up

Safety Features Operator presence system connected to seat, deck clutch and park brake switch. Hand-operated parking brake. Two-post foldable ROPS
Seat Suspension: Molded-vinyl, adjustable seat with armrests. Fore and aft adjustment

Deck Lift Hydraulic

Controls Hand-operated throttle, ignition switch, electric mower clutch.
Cup Holder Single cup holder

Indicators Hour meter, temp guage, oil pressure light, charge light, glow plug light, audible alarm for high engine temperature and low oil pressure

Decks

60" or 72" XR-7™ Side-Discharge or 60" or 72" Rear-Discharge Decks
Deck Lift Raise and lower deck from driver's seat with simple hydraulic-operated deck lift.
Construction Welded steel. Solid 1.5 in x .50 in (3.8 cm x 1.25 cm) steel bars reinforce impact areas on trim edges. Reinforcements welded onto spindle mount areas.Steel deck housing is 5.5 in (14 cm) deep to provide room for high-capacity mowing.

Cutting Heights Height adjustment in .25 in increments from 2 in to 6 in (5 cm to 15 cm).

Mowing Blades Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.
60 in: 20.50 in x 2.50 in x .203 in flat blade, high sail
72 in: 24.50 in x 2.50 in x .230 in flat blade, high sail
Blade Tip Speed 60 in: 18,266 fpm
72 in: 18,964 fpm
Blade Drive V-belt drive to all three spindles. Spring tension idler pulleys.

Spindles Machine ductile housing, 1 in (2.5 cm) diameter high carbon steel shafts and sealed ball bearings.

Discharge Chute Molded Rubber:Over-center design allows for chute to be folded up for improved trailering or to pass thru gates, etc.

Width of Cut 60 in: 60 in (152 cm)
72 in: 72 in (183 cm)

Trim Capacity 60 in XR-7: 9.5 in (24 cm) (left side)
72 in XR-7: 15.5 in (39 cm) (left side)

Accessories

Mulch Kit Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

Snow Blower, Rotary Broom, Front Blade
Debris Blower, Hard Cab, Quick Attach System

Specifications subject to change without notice.

For more information : www.hustlerturf.com HUSTLER
Hustler Turf Equipment • Hesston, Kansas 67062 • 1-800-395-4757

601645 3-08